

12V Battery driven grease gun

Simplify and reduce the time spent in your lubrication process

Designed to minimize the burden of manual lubrication, the TLGB 1262-E battery driven grease gun simplifies and speeds up the lubrication process, making it easier to properly maintain equipment. The three-point base keeps the tool upright and stable without being bulky, allowing access to tight areas and reducing operator fatigue when lubricating.

Featuring an updated powertrain, handle design and enhanced features it is easy to handle and convenient for occasional or daily use, suitable for agricultural, automotive, construction, general maintenance and industrial applications.

- Durable simplicity
- Opens stuck fittings that otherwise would require replacement if using a manual grease gun
- Built-in LED illuminates the work area
- Trapped air inside of the grease gun can be easily removed with the vent valve to restore priming
- Dual-lip follower design enables bulk or cartridge grease delivery and eliminates grease bypass
- High-pressure hose with protective antikink spring guards on each end
- Easily and cleanly filled from drums with
- filler pumps
- Battery charge LED indicator

skf.com | skf.com/agriculture

® SKF and Lincoln are registered trademarks of the SKF Group.

© SKF Group 2022

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

PUB MP/P8 19430 EN · June 2022



Technical data

Designation Grease output Maximum operating pressure Maximum peak pressure Cartridges per battery charge

Length of hose Battery type Battery output Battery capacity Voltage charger, V/Hz Carrying case dimensions Weight (incl. battery) Total weight (incl. case) Accessories TLGB 1261 TLGB 1261 TLGB 20-1 TLGB 20-3

TLGB 1262-E

95 ml/min (3.2 *oz/min*) at 70 bar pressure 241 bar (3 500 *psi*) 551 bar (8 000 *psi*) 2.25 cartridges (200 bar counter pressure) 6.5 cartridges (free flow) 760 mm (30 *in*) Li-lon 12 V 1 500 mAh 200–240 V/ 50–60 Hz 590×108×373 mm (23.2×4.3×14.7 *in*) 2.5 kg (5.5 *lb*) 6 kg (13.2 *lb*)

12 V Li-lon battery 12/24V Battery charger for 12/20V (Li-lon) grease guns Shoulder strap High-pressure hose 900 mm (*36 in*)

