



# Portable Oil Extractor

Alemite's Portable Oil Extractor provides a safe, economical means of emptying fluids from engine crankcases and machine reservoirs with the use of vacuum pressure.

## Features

- Large 24-gallon tank (90 liters) reduces trips to waste container
- Six suction wands with convenient storage caddy
- Pressure relief valve prevents over-pressurization
- Wheel/caster design for portability and stability
- Handy tool tray
- Convenient push handle
- Available sticker kit for easy labeling

## Benefits

- Makes vehicle and equipment servicing easier
- Self-contained design eliminates spills
- External pumping source not required
- Will not over pressurize





## Markets/Applications

Industrial Facilities • Car Dealerships • Quick Lubes • Tire Stores • Garages

## Compatible Fluids

Oils (Motor, Cutting, Gear, Hydraulic) • Windshield Wiper Fluid • Coolants • ATF



**WARNING:** Not for use with flammable or caustic fluids

## Technical Specifications

Part number	8588	
	English Units	Metric Units
Maximum air pressure for emptying	7 psi	0.5 bar
Air pressure for vacuum	100 psi	7 bar
Pressure relief valve	14 psi	1 bar
Tank size	24 gallons	90 liters
Tank usable capacity	16 gallons	61 liters
Suction rate*	1.5 gallons/minute	0.4 liters/minute
Suction wands (diameter x length)		
Metal	0.20 x 27.5 inches	5 x 700 millimeters
	0.24 x 27.5 inches	6 x 700 millimeters
Plastic	0.20 x 27.5 inches	5 x 700 millimeters
	0.24 x 27.5 inches	6 x 700 millimeters
	0.28 x 39.4 inches	7 x 700 millimeters
	0.32 x 27.5 inches	8 x 700 millimeters

\*Waste oil temperature at a minimum of 158°F (70°C) with 0.24-inch (6 mm) diameter wand.  
Air Regulator is recommended.



167 Roweland Drive  
Johnson City, TN 37601  
Toll Free U.S.: 866-4-Alemite  
Toll Free Canada: 800-267-8022  
International: 803-802-0001  
Fax U.S.: 800-648-3917  
Fax Canada: 800-267-2880  
Fax International: 803-802-0192  
www.alemite.com