

# NoWear – a low friction coating for bearings

*Increased reliability and extended machine uptime under severe conditions.*

NoWear coated bearings have a low friction, wear-resistant carbon coating on the contact surfaces inside the bearing.



*NoWear CARB toroidal roller bearing*

## Features

- High wear-resistance – the coating is harder than steel
- High-speed capabilities through unique coating properties
- Very tolerant to contamination
- Tolerant to poor lubrication
- Reduced need of extreme pressure and anti wear additives in the lubricant

## Benefits

- Increased reliability and safety under severe conditions
- Extended machine uptime
- Extended bearing service life – reduced maintenance cost
- Enable freedom in new designs without introducing major design changes
- Energy saving

## Typical applications

- Racing
- Industrial fans
- Mining and mineral processing machines
- Pumps and compressors
- Paper machines
- Marine and offshore applications



© SKF, CARB and NOWEAR are registered trademarks of the SKF Group.

© SKF Group 2011

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

PUB BU/P8 12285 EN · November 2011

This publication supersedes publication 6320.

Certain image(s) used under license from Shutterstock.com

