


Gerotor Pumps

Product series 143

For oil, for use in SKF CircOil centralized lubrication systems



Gerotor pumps, product series 143

SKF gerotor pump units of product series 143 are self-priming positive-displacement pumps with fixed displacement and high efficiency. They are used in SKF CircOil centralized lubrication systems for a variety of tasks and applications, especially in circulating-oil and total-loss lubrication systems.

Fields of application:

- General mechanical and plant engineering
- Shipbuilding and offshore industry
- Paper, printing, and pulp industries
- Heavy industry

Advantages:

- Flexible delivery range from 0.85 to 50 l/min at system pressures up to 50 bar
- Large viscosity range for standard mineral and synthetic lubricating and hydraulic oils from 20 to 1000 mm²/s

- Ambient temperature of 0 to +40 °C
- Low volumetric flow pulsation and thus very smooth running
- Gerotor with a cycloid contour and thus good suction characteristics
- Low-noise
- Gerotor pumps are available in NBR and FKM designs.
- Squirrel cage motors are available in different voltage designs for 50 and 60 Hz
- Compact design
- Modular ordering system (order as a complete pump unit, single pump, or pump with flange and shaft coupling)

Content

Illustration of designs and accessories	3	IEC squirrel cage motors	
Gerotor pumps, product series 143		Principles	14–15
Principles	4–5	Rating plates	15
Technical data	6	Voltage code	16
Order code	7	Technical data	17
Designs, installation drawings, and dimensions		Motor data	17
Gerotor pump	8	Installation drawings and dimensions	18
Gerotor pump+pump flange+shaft coupling	9	Viscosity-temperature relationship of oils	19
Kupplungsmontage	9	Exploded view	20
Motor connection	9	Spare parts	21
Foot and flange design	10–11	Comparison of old and new order No.	22–23
Characteristic curves	12–13		



Note
The technical data in this publication provide for general information. Follow the assembly instructions and any instructions on and accompanying the products when performing assembly, operating, and maintenance.

Technical data and selection and ordering data, including availability, for accessories are subject to change..

Further information

Assembly instructions

951-170-251

You can download the publications as PDF file from the SKF website: skf.com/143

Online configurable and CAD models under skf-lubrication.partcommunity.com

Gerotor pumps, product series 143

Illustration of designs and accessories

Gerotor pump unit in foot design



Gerotor pump unit in flange design



Gerotor



Gerotor pump



Pump flange



Shaft coupling



ICE squirrel cage motor



Gerotor pump+pump flange+shaft coupling



Gerotor pumps, product series 143

Fundamentals

General use

SKF gerotor pump units of product series 143 are used in circulating-oil and total-loss lubrication systems in a flow rate range of 0.85 to 50 l/min. The standard permissible ambient temperature is between 0 and +40 °C. Higher ambient temperatures are possible, though they lead to a reduction in motor performance and thus the delivery rate. The permissible temperature of the pumped medium is between 0 and +80°C. The gerotor pumps are available in NBR and FKM designs.

SKF gerotor pump units feed lubricating and hydraulic oils from a reservoir and into the pipe system of a centralized lubrication system. In doing so, they increase the energy of the pumped medium (pressure increase) to overcome flow resistance in the pipelines (pressure loss), the components (filters, valves, distributors) and the bearings and friction points. SKF gerotor pump units of different types and performance ratings are used depending on the type and size of the centralized lubrication system and the lubricant.

Applications


The main area of application is the broad field of circulating-oil and total-loss lubrication systems for general mechanical engineering and plant engineering applications. Here, the focus is on lubricating and cooling heavily loaded bearings and friction points for a wide range of uses. SKF gerotor pump units are used primarily as lubricating, hydraulic, hydrostatic, and cooling oil pumps. They can be set up either as single pumps or integrated into a reservoir unit. Other areas include the shipbuilding and offshore industry as well as the paper, printing, pulp, and heavy industries.

Delivery rates and characteristic curves

The nominal delivery rates indicated in the catalog refer to the nominal output multiplied by the speed of the motor. The actual delivery rate changes with operating viscosity and back pressure and can be found in the characteristic curve diagrams in the catalog (→ page 12–13). These diagrams are based on the range between 20 and 1000 mm²/s in increments of 20, 140, 750, and 1000 mm²/s. Each gerotor pump has a characteristic curve represented as a function of the delivery rate above the delivery pressure (back pressure).

It is important to note that temperature influences can render lubricating and hydraulic oils extremely thin or viscous. Please consult with us in advance if you will use lubricating and hydraulic oils with an operating viscosity outside the specified range.

SKF CircOil centralized lubrication system



Gerotor pumps, product series 143

Fundamentals

Design (→ Figure 1)

SKF gerotor pump units of product series 143 have a constant displacement volume and one delivery circuit. The annular-toothed feeding element, also referred to as the gerotor, is equipped with a cycloid contour, which creates a large tooth meshing length. This yields a low volumetric flow pulsation and thus very smooth running, low noise production, and good suction characteristics.

SKF gerotor pumps consist primarily of pump housing (1), the shaft (2), the displacement elements toothed rotor (3) and annular gear (4), and the lid (5)..

Suction and displacement process (→ Fig. 1)

The shaft drives the centrally mounted toothed rotor in the indicated direction of rotation via a feather key. The toothed rotor meshes with the outer, eccentrically mounted annular gear and rotates with it. The openings between teeth arising in the suction area (**S**) draw the pumped medium in. The suction and pressure area is separated from the tooth meshing area (**Z**) by a radial gap (**R**) formed by the tooth profiles of the annular gear and the toothed rotor as they slide onto one another. In the pressurized area (**P**), the fluid is fed to the pressure port through increasingly small chambers.

Drive

SKF gerotor pump units of product series 143 are driven by IEC squirrel cage motors sized 63 to 132 in the standard design. The motors are designed for a rated motor voltage of 230/400 V or 400/690 V for 50 networks according to DIN IEC 60038. The normal coils used here in motors with performance ≤ 0.75 kW are designed for the wide voltage range. The normal coils in motors with performance ≥ 0.75 kW are tailor-made and meet the IE3 efficiency level according to EU Directive 2009/125/EC. Special voltage versions with special coils for 50 Hz and 60 Hz networks are available for order.

The standard design of the motors comes with a terminal box. Motors with UL/CSA certification are available. Further certifications are available on request.

Shaft coupling

The shaft couplings are designed as curved-tooth couplings. Curved-tooth couplings are flexible shaft connections for positive torque transmission. The material combination of steel hub and polyamide sleeve used for the curved-tooth couplings permits maintenance-free continuous duty with very low friction on the teeth. They, therefore, do not require any lubrication or maintenance and are nearly wear-free in operation.

Installation

SKF gerotor pump units of product series 143 can be installed both horizontally and vertically. Foot or flange versions are available for each gerotor pump unit design.

When the gerotor pump unit is set up separately from the reservoir, the suction port on the pump can be connected to a reservoir at a higher position (max. 2000 mm).

To flange the gerotor pump unit to a reservoir horizontally below the oil level, use a sealed pump in a special design. Please consult our Engineering department in advance.

In its design as a pump with flange and coupling, various technical designs of customer-specific electrical motors can be used. The flange allows for the installation of all IEC standard motors with a flange according to DIN EN 50347, design FT (with threaded holes). See the drawings in this publication for the geometric dimensions of the flange.

If only gerotor pumps without a motor are used, for example as an integrated/attached pump on a machine housing, ensure that no radial or axial load is applied to the drive shaft. The pumps can be installed in any position.







Fig. 1

Installation



Flange design

Foot design



Gerotor pumps, product series 143

Technical data

Gerotor pump unit in foot design



Gerotor pump unit in flange design



Gerotor pump



Table 1

Technical data

Lubricant	standard mineral, synthetic lubricating and hydraulic oils
Operating viscosity	20–1000 mm ² /s
Flow range	0,85–50 l/min
Operating pressure	up to 50 bar
Ambient temperature range	0 to +40 °C
Medium temperature range	0 to +80 °C
Protection class acc. to DIN EN 60529	IP 54
Operating noise level	60 dBA
Drive speed depending on design	1400 and 2800 min ⁻¹
Suction head, max.	1000 mm
Varnishing	RAL 7024 graphite grey, special painting optional
Duty type per VDE 0530	S1
Sealing material	NBR, FKM
Mounting position	horizontal, vertical
Materials	
Pump housing	hydraulic cast (pressure-proof) with good wear and antifriction properties
Gerotor insert	sintered material
Shafts	low-deformation steels, case-hardened
Bearing	SKF plain bearing



General notes on usage

During commissioning, pay attention to the pump's direction of rotation. See the rating plate and motor rotation arrow on the pump.

If using the pumps in systems without any open pressure lines, provide pressure-regulating valves to limit the maximum pressure of the system.

The selected cross-section of the intake tube must be equal to or greater than the cross-section of the pump's suction port.

SKF Lubrication Systems Germany GmbH recommends the use of filters for trouble-free operation of the pumps or pump units. Effective filtration prevents malfunctions while also increasing the service life of the pumps. A pumped medium of at least the purity class 20/17/14 according to ISO 4406(c) is recommended. This corresponds to the U.S. standard NAS code (1638) class 8 and SAW AS 4059 class 8. A filter rating of approx. 5 - 10 µm meets this requirement. The filter rating used is always based on the most sensitive component in the entire system. This is not necessarily the pump.

Gerotor pumps, product series 143


Order code	1	4	3	-	1							-				+			
Product series 143																			
Model design																			
1 = Motor in foot design (IMB34) 2 = Motor in flange design (IMB14) 3 = Gerotor pump+pump flange+shaft coupling (without motor) 4 = Only gerotor pump (without motor) ¹⁾																			
Sealing design																			
F = FKM N = NBR																			
Code for pump design ¹⁾																			
→ Table 2																			
Terminal box position ²⁾ as seen from shaft extension of drive side																			
R = Right O = Top X = On motor in flange design (IMB14), Terminal box position on suction port side of pump																			
Motor certification ²⁾ (others on request)																			
A = CE (Europe) B = UL/CSA (USA/Canada)																			
Voltage code ²⁾																			
→ page 16																			
2) Not applicable on designs without motor																			
Table 2																			
Code for pump design																			
Code ¹⁾	Nominal delivery rate	Back pressure max.	Motor drive power	Permissible operating viscosity	Frame size	Number of poles													
–	l/min	bar	kW	mm ² /s	–	–													
B03C	0.85	30	0.18	20–1000	63	4													
D03E	1.70	30	0.37	20–1000	71	2													
F02D	2.50	20	0.25	20–1000	71	4													
F05F	2.50	50	0.55	20–1000	80	4													
H02F	5.25	20	0.55	20–1000	80	4													
H05J	5.25	50	1.10	20–1000	90	4													
K02H	9.00	20	0.75	20–1000	80	4													
K05J	9.00	50	1.10	20–1000	90	4													
M02H	12.50	20	0.75	20–1000	80	4													
M05K	12.50	50	1.50	20–1000	90	4													
P02K	19.00	20	1.50	20–1000	90	4													
R02M	30.00	20	3.00	20–1000	100	2													
R03M	30.00	30	3.00	20–750	100	2													
R03N	30.00	30	4.00	20–1000	112	2													
T02M	40.00	20	3.00	20–750	100	2													
T03N	40.00	30	4.00	20–1000	112	2													
V02N	50.00	20	4.00	20–1000	112	2													
V03N	50.00	30	4.00	20–750	112	2													
V03P	50.00	30	5.50	20–1000	132	2													

1) For model design 4 delete item 4 of the code for the pump design, also the following items of the code.
2) Nominal delivery rate at motor speed 1400/2800 min⁻¹ acc. to number of motor pins.

Order example

143-11ND03E-RA+1GD

- Gerotor pump unit PS 143
- Motor in foot design
- Sealing NBR
- Nominal delivery rate 1.7 l/min
- Back pressure 30 bar
- Motor index 0.37 kW
- Terminal box on right
- Motor certification CE
- 230 / 400 V, 50 Hz
460 V, 60 Hz



If ordering the gerotor pump+pump flange+shaft coupling (model design 3) the identification letters of terminal box position, motor certification and voltage code is omitted

Example: **143-13ND03E**


If ordering the gerotor pump (model design 4) the identification letters of terminal box position, motor certificate and voltage code is omitted, also item 4 of the code for the pump design

Example: **143-14ND03**

Gerotor pumps, product series 143

Gerotor pump design, technical data and dimensions

Figure 2



Nominal delivery rate [l/min]	Back pressure max. [bar]	Perm. viscosity range [mm²/s]	Char. curve No. 1)	Nominal output [cm³/rev.]	Speed [min⁻¹]	Required drive power [kW]	Suction port S	Pressure port P	Gerotor pump (→ Figure 2)																	
									Design N (NBR)/ F (FKM)			Dimensions [mm]														
									Order No. 4)	A	B	C	D	ØE	F	H	ØK	ØL	ØM	ØN	ØN_1	T	W_1	W_2	Fig.	
0.85	30	20-1000	1	0.61	1400	0.18	G1/4 12 deep	G1/4 12 deep	19	143-14...B03	49	25	3	9	36 _{h7}	2	12.5	60	48	6.6	8 _{h5}	-	8.8	14	2	1/4
1.7	30	20-1000	2	0.61	2800	0.37	G1/4 12 deep	G1/4 12 deep	19	143-14...D03	49	25	3	9	36 _{h7}	2	12.5	60	48	6.6	8 _{h5}	-	8.8	14	2	1/4
2.5	20	20-1000	3	1.79	1400	0.25	G3/8 12 deep	G3/8 12 deep	23	143-14...F02	62	28	3	12	45 _{h7}	4	17	74	56	6.6	12 _{g5}	12 _{g5}	13.5	18.5	2.5	2/5
2.5	50	20-1000	3	1.79	1400	0.55	G3/8 12 deep	G3/8 12 deep	23	143-14...F05	62	28	3	12	45 _{h7}	4	17	74	56	6.6	12 _{g5}	12 _{g5}	13.5	18.5	2.5	2/5
5.25	20	20-1000	4	3.75	1400	0.55	G1/2 14.5 deep	G1/2 14.5 deep	27	143-14...H02	69	30	3	12.7	56 _{h7}	5	18.5	88	70	6.6	14 _{g5}	14 _{g5}	16	20.5	2.5	3/5
5.25	50	20-1000	4	3.75	1400	1.1	G1/2 14.5 deep	G1/2 14.5 deep	27	143-14...H05	69	30	3	12.7	56 _{h7}	5	18.5	88	70	6.6	14 _{g5}	14 _{g5}	16	20.5	2.5	3/5
9	20	20-1000	5	6.44	1400	0.75	G1/2 14.5 deep	G1/2 14.5 deep	27	143-14...K02	77	30	3	12.7	56 _{h7}	5	20	88	70	6.6	14 _{g5}	14 _{g5}	16	20.5	2.5	3/5
9	50	20-1000	5	6.44	1400	1.1	G1/2 14.5 deep	G1/2 14.5 deep	27	143-14...K05	77	30	3	12.7	56 _{h7}	5	20	88	70	6.6	14 _{g5}	14 _{g5}	16	20.5	2.5	3/5
12.5	20	20-1000	6	8.93	1400	0.75	G3/4 16 deep	G3/4 16 deep	33	143-14...M02	89	30	3	12.7	56 _{h7}	5	22	88	70	6.6	14 _{g5}	14 _{g5}	16	20.5	2.5	3/5
12.5	50	20-1000	6	8.93	1400	1.5	G3/4 16 deep	G3/4 16 deep	33	143-14...M05	89	30	3	12.7	56 _{h7}	5	22	88	70	6.6	14 _{g5}	14 _{g5}	16	20.5	2.5	3/5
19	20	20-1000	7	13.6	1400	1.5	G1 18 deep	G1 18 deep	40	143-14...P02	100	30	3	21.5	56 _{h7}	5	25	98	80	8.5	16 _{g5}	16 _{g5}	18	21.5	2.5	3/5
30	20	20-1000	8	10.74	2800	3	G1 18.5 deep	G1 18.5 deep	41	143-14...R02	108	42	4	23.5	80 _{f7}	6	30	119	104	8.5	19 _{g6}	22	21.5	36.5	-	3/6
30	30	20-750	8	10.74	2800	3	G1 18.5 deep	G1 18.5 deep	41	143-14...R03	108	42	4	23.5	80 _{f7}	6	30	119	104	8.5	19 _{g6}	22	21.5	36.5	-	3/6
30	30	20-1000	8	10.74	2800	4	G1 18.5 deep	G1 18.5 deep	41	143-14...R03	108	42	4	23.5	80 _{f7}	6	30	119	104	8.5	19 _{g6}	22	21.5	36.5	-	3/6
40	20	20-750	9	14.36	2800	3	G1 18.5 deep	G1 18.5 deep	41	143-14...T02	108	42	4	23.5	80 _{f7}	6	30	119	104	8.5	19 _{g6}	22	21.5	36.5	-	3/6
40	30	20-1000	9	14.36	2800	4	G1 18.5 deep	G1 18.5 deep	41	143-14...T03	108	42	4	23.5	80 _{f7}	6	30	119	104	8.5	19 _{g6}	22	21.5	36.5	-	3/6
50	20	20-1000	10	17.87	2800	4	G1 1/4 20.5 deep	G1 18.5 deep	41/51	143-14...V02	111	42	4	23.5	80 _{f7}	6	30	119	104	8.5	19 _{g6}	22	21.5	36.5	-	3/6
50	30	20-750	10	17.87	2800	4	G1 1/4 20.5 deep	G1 18.5 deep	41/51	143-14...V03	111	42	4	23.5	80 _{f7}	6	30	119	104	8.5	19 _{g6}	22	21.5	36.5	-	3/6
50	30	20-1000	10	17.87	2800	5.5	G1 1/4 20.5 deep	G1 18.5 deep	41/51	143-14...V03	111	42	4	23.5	80 _{f7}	6	30	119	104	8.5	19 _{g6}	22	21.5	36.5	-	3/6

1) → see page 12

Gerotor pumps, product series 143

Gerotor pump+pump flange+shaft coupling design, technical data and dimensions




Figure 5




Table 3

Gerotor pump + pump flange (\rightarrow Figure 3)												Coupling assembly (\rightarrow Figure 4)						Motor connection (\rightarrow Figure 5)										
Design N (NBR) / F (FKM) Order No. 5)	Maße [mm]												Fig. 7 (A1)	Fig. 8 (B1)	Fig. 9 (C1)	Fig. 9 (D1)	Fig. 9 (E1)	Fig. 9 (F1)	Frame size			\varnothing M	SM	\varnothing D	E	EB	GA	F
	\varnothing PM	\varnothing PN	L1	L2	L3	\varnothing FM1	\varnothing M1	\varnothing SY	\varnothing MZ	SZ	F	\varnothing N	T	\varnothing M	SM	\varnothing D	\varnothing E	\varnothing EB	\varnothing GA	\varnothing F								
143-13...B03C	120	72	53.5	104	14	—	—	85	M6	28	42	—	—	—	—	63	80	3	100	M6 ₈ tief	11 _{j6}	23	18	12.5	4			
143-13...D03E	140	95	55.5	109	12	—	—	—	115	M8	28	42	—	—	—	—	71	95	3	115	M8 ₁₂ tief	14 _{j6}	30	25	16	5		
143-13...F02D	140	95	65	127	17	—	—	—	115	M8	31	51	—	—	—	—	71	95	3	115	M8 ₁₂ tief	14 _{j6}	30	25	16	5		
143-13...F05F	160	110	77	137	15	—	—	—	130	M8	—	—	31	40	—	—	80	110	3.5	130	M8 ₁₂ tief	19 _{j6}	40	32	21.5	6		
143-13...H02F	160	110	78.5	144	15	—	—	—	130	M8	—	—	31	40	—	—	80	110	3.5	130	M8 ₁₂ tief	19 _{j6}	40	32	21.5	6		
143-13...H05J	160	110	85.5	153	17	—	—	—	130	M8	—	—	31	49	—	—	90	110	3.5	130	M8 ₁₃ tief	24 _{j6}	50	40	27	8		
143-13...K02H	160	110	80	152	15	—	—	—	130	M8	—	—	31	40	—	—	80	110	3.5	130	M8 ₁₂ tief	19 _{j6}	40	32	21.5	6		
143-13...K05J	160	110	87	161	17	—	—	—	130	M8	—	—	31	49	—	—	90	110	3.5	130	M8 ₁₃ tief	24 _{j6}	50	40	27	8		
143-13...M02H	160	110	82	164	15	—	—	—	130	M8	—	—	31	40	—	—	80	110	3.5	130	M8 ₁₂ tief	19 _{j6}	40	32	21.5	6		
143-13...M05K	160	110	89	173	17	—	—	—	130	M8	—	—	31	49	—	—	90	110	3.5	130	M8 ₁₃ tief	24 _{j6}	50	40	27	8		
143-13...P02K	160	110	92	184	17	—	—	—	130	M8	—	—	30	50	—	—	90	110	3.5	130	M8 ₁₃ tief	24 _{j6}	50	40	27	8		
143-13...R02M	200	144.6	124	218	16	250	225	9	165	—	—	—	—	46	60	100	130	3.5	165	M10 ₁₂ tief	28 _{j6}	60	50	31	8			
143-13...R03M	200	144.6	124	218	16	250	225	9	165	—	—	—	—	46	60	100	130	3.5	165	M10 ₁₂ tief	28 _{j6}	60	50	31	8			
143-13...R03N	200	144.6	124	218	16	250	225	9	165	—	—	—	—	46	60	100	130	3.5	165	M10 ₁₂ tief	28 _{j6}	60	50	31	8			
143-13...T02M	200	144.6	124	218	16	250	225	9	165	—	—	—	—	46	60	100	130	3.5	165	M10 ₁₂ tief	28 _{j6}	60	50	31	8			
143-13...T03N	200	144.6	124	218	16	250	225	9	165	—	—	—	—	46	60	100	130	3.5	165	M10 ₁₂ tief	28 _{j6}	60	50	31	8			
143-13...V02N	200	144.6	124	221	16	250	225	9	165	—	—	—	—	46	60	112	130	3.5	165	M10 ₁₂ tief	28 _{j6}	60	50	31	8			
143-13...V03N	200	144.6	124	221	16	250	225	9	165	—	—	—	—	46	60	112	130	3.5	165	M10 ₁₂ tief	28 _{j6}	60	50	31	8			
143-13...V03P	200	145	154	251	16	250	225	9	165	—	—	—	—	48	88	132	130	3.5	165	M10 ₁₂ tief	38 _{k6}	80	70	41	10			


5) Supplement the order No. with the code letter for the desired seal design. Seal design NBR (N) or FKM (F).

Gerotor pumps, product series 143

Foot and flange designs, technical data and dimensions

Figure 6

Foot design (type IMB34)



Delivery rate [l/min]	Back pres- sure [bar]	Viscosity range max.	Char. curve No. ¹⁾	Food design N (NBR) / F (FKM) Order No. ²⁾ ³⁾	Flange design N (NBR) / F (FKM) Order No. ²⁾ ³⁾	Nominal output [cm³/U]	Suction port	Pressure port	Dimensions [mm] (→ Drawing 6+7)						
									P	ØPD	ØSD	ØPN	ØPF	ØFM1	ØMZ
0,85	30	20-1000	1	143-11...B03C-R...	143-12...B03C-X...	0,61	G1/4 12 deep	G1/4 12 deep	19	19	72	120	-	100	-
1,7	30	20-1000	2	143-11...D03E-R...	143-12...D03E-X...	0,61	G1/4 12 deep	G1/4 12 deep	19	19	95	140	-	115	-
2,5	20	20-1000	3	143-11...F02D-R...	143-12...F02D-X...	1,79	G3/8 12 deep	G3/8 12 deep	23	23	95	140	-	115	-
2,5	50	20-1000	3	143-11...F05F-R...	143-12...F05F-X...	1,79	G3/8 12 deep	G3/8 12 deep	23	23	110	160	-	130	-
5,25	20	20-1000	4	143-11...H02F-R...	143-12...H02F-X...	3,75	G1/2 14,5 deep	G1/2 14,5 deep	27	27	110	160	-	130	-
5,25	50	20-1000	4	143-11...H05J-R...	143-12...H05J-X...	3,75	G1/2 14,5 deep	G1/2 14,5 deep	27	27	110	160	-	130	-
9	20	20-1000	5	143-11...K02H-R...	143-12...K02H-X...	6,44	G1/2 14,5 deep	G1/2 14,5 deep	27	27	110	160	-	130	-
9	50	20-1000	5	143-11...K05J-R...	143-12...K05J-X...	6,44	G1/2 14,5 deep	G1/2 14,5 deep	27	27	110	160	-	130	-
12,5	20	20-1000	6	143-11...M02H-R...	143-12...M02H-X...	8,93	G3/4 16 deep	G3/4 16 deep	33	33	110	160	-	130	-
12,5	50	20-1000	6	143-11...M05K-R...	143-12...M05K-X...	8,93	G3/4 16 deep	G3/4 16 deep	33	33	110	160	-	130	-
19	20	20-1000	7	143-11...P02K-R...	143-12...P02K-X...	13,6	G1 18 deep	G1 18 deep	40	40	110	160	-	130	-
30	20	20-1000	8	143-11...R02M-R...	143-12...R02M-X...	10,74	G1 18,5 deep	G1 18,5 deep	41	41	144,6	200	250	165	225
30	30	20-750	8	143-11...R03M-R...	143-12...R03M-X...	10,74	G1 18,5 deep	G1 18,5 deep	41	41	144,6	200	250	165	225
30	30	20-1000	8	143-11...R03N-O...	143-12...R03N-X...	10,74	G1 18,5 deep	G1 18,5 deep	41	41	144,6	200	250	165	225
40	20	20-750	9	143-11...T02M-R...	143-12...T02M-X...	14,36	G1 18,5 deep	G1 18,5 deep	41	41	144,6	200	250	165	225
40	30	20-1000	9	143-11...T03N-O...	143-12...T03N-X...	14,36	G1 18,5 deep	G1 18,5 deep	41	41	144,6	200	250	165	225
50	20	20-1000	10	143-11...V02N-O...	143-12...V02N-X...	17,87	G1 1/4 20,5 tief	G1 18,5 tief	41	51	144,6	200	250	165	225
50	30	20-750	10	143-11...V03N-O...	143-12...V03N-X...	17,87	G1 1/4 20,5 tief	G1 18,5 tief	41	51	144,6	200	250	165	225
50	30	20-1000	10	143-11...V03P-R...	143-12...V03P-X...	17,87	G1 1/4 20,5 tief	G1 18,5 tief	41	51	145	200	250	165	225

1) → see page 12

2) Supplement the order No. with the code letter for the desired seal design. Seal design NBR (N) or FKM (F).

3) Supplement the order No. with the code letter for the desired motor certification (→ page 7) and the voltage code (→ page 16).

For associated motor data → page 17.

Gerotor pumps, product series 143

Foot and flange designs, technical data and dimensions

Figure 7




Table 4

Dimensions [mm] (→ Drawing 6+7)

SZ	ØSYL1	L2	L3	A	AA	AB	ØAC	AD	AF	B	BA	BB	C	H	HA	HD	HH	K	K1	U	XA	XB	L	
M6	-	36,5	104	14	100	22	120	124	107	84,5	80	-	95	40	63	7,5	-	61	Ø7	-	1xM25x1,5	92	92	309,5
M8	-	36,5	109	12	112	32	138	124	107	84,5	90	-	116	45	71	11	-	61	Ø8	-	1xM25x1,5	90	90	319
M8	-	45	127	17	112	24	135	139	115	92	90	-	114	45	71	8	-	67	Ø7	-	1xM25x1,5	90	90	337
M8	-	45	137	15	125	30,5	150	159	149,5	112,5	100	32	118	50	80	8	229,5	73	9,5	13,5	1xM25x1,5	123	119,5	389
M8	-	50,5	144	15	125	30,5	150	159	149,5	112,5	100	32	125	50	80	8	229,5	73	9,5	13,5	1xM25x1,5	123	119,5	396
M8	-	50,5	153	17	140	30,5	165	178	154,5	117,5	100	33	143	56	90	10	244,5	78,5	10	14	1xM25x1,5	123	119,5	450
M8	-	57	152	15	125	30,5	150	159	149,5	112,5	100	32	118	50	80	8	229,5	73	9,5	13,5	1xM25x1,5	123	119,5	439
M8	-	57	161	17	140	30,5	165	178	154,5	117,5	100	33	143	56	90	10	244,5	78,5	10	14	1xM25x1,5	123	119,5	458
M8	-	67	164	15	125	30,5	150	159	149,5	112,5	100	32	118	50	80	8	229,5	73	9,5	13,5	1xM25x1,5	123	119,5	451
M8	-	67	173	17	140	30,5	165	178	154,5	117,5	100	33	143	56	90	10	244,5	78,5	10	14	1xM25x1,5	123	119,5	510
M8	-	75	184	17	140	30,5	165	178	154,5	117,5	100	33	143	56	90	10	244,5	78,5	10	14	1xM25x1,5	123	119,5	521
Ø11	9	78	218	16	160	42	196	198	166	125,5	140	37,5	176	63	100	12	266	96,5	12	16	2xM32x1,5	112	135	588,5
Ø11	9	78	218	16	160	42	196	198	166	125,5	140	37,5	176	63	100	12	266	96,5	12	16	2xM32x1,5	112	135	588,5
Ø11	9	78	218	16	190	46,0	226	222	177	136,5	140	37,5	176	70	112	12	289	96	12	16	2xM32x1,5	112	135	572
Ø11	9	78	218	16	160	42	196	198	166	125,5	140	37,5	176	63	100	12	266	96,5	12	16	2xM32x1,5	112	135	588,5
Ø11	9	78	218	16	190	46	226	222	177	136,5	140	37,5	176	70	112	12	289	96	12	16	2xM32x1,5	112	135	572
Ø11	9	81	221	16	190	46	226	222	177	136,5	140	37,5	176	70	112	12	289	96	12	16	2xM32x1,5	112	135	575
Ø11	9	81	221	16	190	46	226	222	177	136,5	140	37,5	176	70	112	12	289	96	12	16	2xM32x1,5	112	135	575
Ø11	9	81	251	16	216	53	256	262	202	159,5	140	38	180	89	132	15	-	115,5	12	16	2xM32x1,5	130	155	636

Gerotor pumps, product series 143

Characteristic curves

Chart 1

Operating viscosity 20 mm²/s, 50 Hz

Delivery rate Q [l/min]





Chart 2

Operating viscosity 140 mm²/s, 50 Hz

Delivery rate Q [l/min]



Legend to diagrams 1–4:



- Characteristic curve 1: 0.85 l/min
- Characteristic curve 2: 1.7 l/min
- Characteristic curve 3: 2.5 l/min
- Characteristic curve 4: 5.25 l/min
- Characteristic curve 5: 9 l/min
- Characteristic curve 6: 12.5 l/min
- Characteristic curve 7: 19 l/min
- Characteristic curve 8: 30 l/min
- Characteristic curve 9: 40 l/min
- Characteristic curve 10: 50 l/min

Tolerances: VDMA 24284-II

For connection with a frequency of 60 Hz, the speed and the volumetric flow are increased by 20% (compared to the table specifications, basis 50 Hz).

Gerotor pumps, product series 143

Characteristic curves



Legend to diagrams 1–4:

- Characteristic curve 1: 0.85 l/min
- Characteristic curve 2: 1.7 l/min
- Characteristic curve 3: 2.5 l/min
- Characteristic curve 4: 5.25 l/min
- Characteristic curve 5: 9 l/min
- Characteristic curve 6: 12.5 l/min
- Characteristic curve 7: 19 l/min
- Characteristic curve 8: 30 l/min
- Characteristic curve 9: 40 l/min
- Characteristic curve 10: 50 l/min

Tolerances: VDMA 24284-II

For connection with a frequency of 60 Hz, the speed and the volumetric flow are increased by 20% (compared to the table specifications, basis 50 Hz).

IEC squirrel cage motors

Fundamentals

General information

The standard design of SKF gerotor pump units of product series 143 is driven by IEC asynchronous motor. The motors are used in sizes 63 to 132, in 2-pole and 4-pole designs. They meet the relevant IEC/EN standards both mechanically and electrically. The standard design of the motors comes with a terminal box. The motors bear a CE marking in accordance with Low Voltage Directive 2014/35/EC. There is no CE marking with respect to Machinery Directive 2006/42/EC and EMC Directive 2014/30/EC because asynchronous motors do not fall under the scope of these Directives.

Special provisions

The motors can be ordered in UL and CSA-compliant versions and are approved by UL (Underwriter Laboratories). These motors have an electrical design according to NEMA MG1-12 and meet the required NEMA efficiency classes. The UL approval is stored on the rating plate of the motor.

Other approvals on request.

Types

The motors are used exclusively in the types IM B34 and IM B14. The type is indicated according to Code I, DIN EN 60034-7 on the rating plate.

IM B34: Shaft horizontal, feet on floor

IM B14: Shaft horizontal, no feet

Rated voltage, frequency and power output

The motors are configured as standard for a rated motor voltage in accordance with IEC 38 of 230 V, 400 V or 690 V for 50 Hz networks (standard winding). Motors for other voltages and frequencies (non-standard winding) are available at additional cost.

The voltage deviation permitted in operation for the aforementioned rated motor voltages and for special voltages is $\pm 5\%$ for range A (continuous duty operation) and $\pm 10\%$ for range B (short-time duty operation), as specified in EN 60034-1. The permitted frequency deviation is $\pm 2\%$ for range A and $-5/+3\%$ for range B. For supply voltages that are 95% or 105% of the rated motor voltage, the tolerances described in EN 60034-1 are met. Furthermore, motor temperature is allowed to exceed the permitted temperature rise limit by 10 K. The percentile specifications for the permitted voltage and frequency deviations are not stamped onto the rating plate of the motor. The presence of the CE mark on the motor rating plate, accompanied by a reference to standard EN 60034, guarantees that these requirements have been incorporated by the motor manufacturer during configuration of the motor.

The motors are designed for a rated motor voltage of 230/400 V or 400/690 V for 50 Hz networks according to DIN IEC 60038. The standard windings used for this are point-wound. Motors with power $\leq 0.75 \text{ kW}$ correspond to efficiency class IE2, motors with power $\geq 0.75 \text{ kW}$ correspond to efficiency class IE3 according to EU Directive 2009/125/EG, Regulation (EU) 2019/1781. Special voltages with abnormal windings for 50 Hz and 60 Hz networks are available to order.

The stated rated outputs and operating values apply to duty type S1 in accordance with EN 60034-1 at the stated rated frequency, rated voltage, a coolant temperature of 40°C maximum and a site installation altitude up to 1 000 metres above sea level. Enquiries for motors for operating conditions other than those mentioned are welcome, on the understanding that these will incur additional costs.

Circuit

The phase belts of the motor that are laid on the terminal board can be interconnected in two different connection systems:

Star connection

In the star connection, the coil ends U2, V2, and W2 are interconnected on the terminal board, creating the neutral point. Mains power is connected on the free connection ports of the coil ends U1, V1, and W1 on the terminal board.

Delta connection

In the delta connection, the end of the phase belt is interconnected with the beginning of the next phase belt. (U2 to V1, V2 to W1, W2 to U1). Mains power is connected at the connection points on the terminal board.

IEC squirrel cage motors

Fundamentals

Cooling method

The motors are designed for cooling method IC 411 (surface cooling).

Temperature class

The insulation on the motor coils is designed for temperature class 155 (F). When utilized at their performance rating, the motors meet temperature class 130 (B). Given a coolant temperature of 40°C, the power reserve is thus approx. +10%; when operated at their performance rating, the temperature reserve is approx. +20 K.

Protection class

The motors are designed for protection class IP55 according to DIN EN 60034-5.


Touch and foreign object protection:

Provides complete protection against contacting or getting close to such parts, as well as against touching moving parts within the housing. Provides protection against the ingress of damaging amounts of dust deposits. Water protection: A jet of water from a nozzle and aimed at the motor from all directions has no adverse effect.

Terminal box

The degree of protection of the terminal boxes is IP55. The terminal box location on the standard engines is on the right at Blick on the drive side. The exception is the 2-pole motor size 112 (4.0 kW), at which the terminal box is on the left. For design reasons, the standard is mounted at the top. Special motors with different terminal box positions than standard motors are available on request. The position of the openings for the cable entry can be adjusted to the existing connection options by rotating the terminal box by 90°. The thread of the cable entry has 1x metric thread M25×1.5 for sizes 63 to 90. Sizes 100 to 132 have 2x M32×1.5. The clipboard is fundamental 6-pole design.

Rating plates



- 1 Type of machine:
three-phase low-voltage motor
- 2 Article no.
- 3 factory number
(ID no., serial number)
- 4 Design
- 5 Degree of protection
- 6 Rated voltage [V] and winding circuit
- 7 Frequency [Hz]
- 8 Rated current [A]
- 9 Rated power [kW]
- 10 Power factor ($\cos \phi$)
- 11 efficiency
- 12 Rated speed [min^{-1}]
- 13 IE efficiency class
- 14 Standards and regulations
- 15 Machine weight [kg]
- 16 heat class
- 17 size
- 18 Additional information (optional)
- 19 operating temperature range
- 20 installation altitude
(only if greater than 1000 m)
- 21 Customer data (optional)
- 22 Date of manufacture YYMM
- 23 half-key balancing
- 24 Code Letter „CL“
- 25 Engine Type Number (MT)
- 26 IEC standard series
Power 50Hz
(P50/50Hz) 400A
- 27 IEC standard series
Power 50Hz 690A
- 28 Equivalent power 60 Hz with the same utilization as IEC standard series 50 Hz
- 29 IEC standard series performance
60Hz (P50/60Hz)
- 30 manufacturer address
- 31 Ship Certificates
- 32 Information optional
- 33 stock size
- 34 Relubrication data optional

IEC squirrel cage motors

Voltage code

Table 5

Voltages and frequencies of different countries

Voltage	Voltage tolerance (DIN EN 60034-1)		Voltage key and approval		Country code
	Range A	Range B	CE	UL/CSA	
50 Hz	200 / 345	±5	±10	+1GF	+1GF JP, HK
	220 / 380	±5	±10	+1GP	+1GP CN, RU, TR, IQ, IR, ID, IN, TH, VN, AR, CL, EG, DZ, LY, AF
	230 / 400	±5	±10	+1GD	+1GD EU, IL, PK, ZA, AE, BD, MM
	240 / 415	±5	±10	+1GQ	+1GQ UK, IN, IQ, MY, AU, NZ, SG, KW, QA
	255 / 440	±5	±10	+MFN	+MFN
	500	±5	±10	+1HQ	+1HQ
	305 / 525	±5	±10	+MMP	- ZA
	380 / 660	±5	±10	+1GH	- CN, RU, TR, IQ, IR, ID, IN, TH, VN, AR, CL
	400 / 690	±5	±10	+1GK	-
	415 Δ (P ≥ 5,5 kW)	±5	±10	+1GL ¹⁾	- UK, IN, IQ, MY, AU, NZ, SG
60 Hz	500 Δ (P ≥ 5,5 kW)	±5	±10	+1LL ³⁾	+1LL ³⁾
	200 / 345	±5	±10	+1GG	+1GG JP
	220 / 380	±5	±10	+MDP	+MDP BR, KP, KR, PE, MX, SA, TW, VE, BO
	230 / 400	±5	±10	+1GR	+1GR
	240 / 415	±5	±10	+1KS	+1KS
	400 / 690	±5	±10	+585	+585
	440Y	±5	±10	+1GP)	+1GP MX, PA, PH
	460Y	±5	±10	+1GP	+1GD US, CA, MX
	480Y	±5	±10	+GQ	+1GQ CA
	575Y	±5	±10	+1HQ	+1HQ
	440 Δ	±5	±10	+1GH	- MX, PA, PH
	460 Δ	±5	±10	+1GK	- US, CA, MX
	460 Δ (P ≥ 5,5 kW)	±5	±10	-	+1KG ²⁾
	480 Δ (P ≥ 5,5 kW)	±5	±10	+1GL ¹⁾	- CA
	575 Δ (P ≥ 5,5 kW)	±5	±10	+1LL ³⁾	+1LL ³⁾

AE = United Arab Emirates

AF = Afghanistan

AR = Argentina

AU = Australia

BO = Bolivia

BR = Brazil

CA = Canada

CL = Chile

CN = China

DZ = Algeria

EG = Egypt

EU = Europe

HK = Hong Kong

ID = Indonesia

IL = Israel

IN = India

IQ = Iraq

IR = Iran

JP = Japan

KR = Korea

KW = Kuwait

LY = Libya

MX = Mexico

MY = Malaysia

NZ = New Zealand

PA = Panama

PE = Peru

PH = Philippines

PK = Pakistan

QA = Qatar

RU = Russia

SA = Saudi Arabia

SG = Singapore

TH = Thailand

TR = Turkey

TW = Taiwan

UK = United Kingdom

US = USA

VE = Venezuela

VN = Vietnam

ZA = South Africa

Note: Motors with a performance rating of ≥0.75 kW must be designed for efficiency class IE3.

(others available on request)

1) P ≥ 5,5 kW not for UL/CSA

2) P ≥ 5,5 kW not for UL/CSA

3) P ≥ 5,5 kW

Voltage code texts

+1GD 230 / 400 V, 50 Hz; 460 V, 60 Hz

+1GF 200 / 345 V, 50 Hz

+1GG 200 / 345 V, 60 Hz

+1GH 380 / 660 V, 50 Hz; 440 V, 60 Hz

+1GK 400 / 690 V, 50 Hz; 460 V, 60 Hz

+1GL 415 V, 50 Hz, Δ; 480 V, 60 Hz, Δ¹⁾

+1GP 220 / 380 V, 50Hz ; 440 V, 60 Hz

+1GQ 240 / 415 V, 50 Hz; 480 V, 60 Hz

+1GR 230 / 400 V, 60 Hz

+1HQ 290 / 500 V, 50 Hz; 330 / 575 V, 60 Hz

+1KG 400 V, 50 Hz, Δ; 460 V, 60 Hz, Δ²⁾

+1KS 240 / 415V, 60 Hz

+1LL 500 V, 50 Hz, Δ; 575 V, 60 Hz, Δ³⁾

+MDP 220 / 380 V, 60 Hz

+MFN 255 / 440 V, 50 HZ

+MMP 305 / 525 V, 50 Hz

+585 400 / 690 V, 60 Hz

IEC squirrel cage motors

Technical data

Squirrel cage motor in foot design		Table 6											
Technical data													
Type	Foot design IM B34, Flange design IM B14 IP55												
Protection class	Temperature class												
Temperature class	Duty type												
Duty type	Temperature range											-20 to +40 °C	
Temperature range	Max. site altitude											1000 m above sea level	
Max. site altitude	Cooling method											IC 411 (surface cooling with fan))	
Cooling method	Temperature monitoring											none	
Temperature monitoring	Terminal box material											Metal	

Table 7															
Code for pump design															
Frame size	Number of poles	Flange-design (with threaded hole) ¹⁾	50 Hz				60 Hz				Rated power ²⁾	Speed	Rated current ^Δ	Rated current ^Y	
			Weight	Rated voltage ^Δ	Rated voltage ^Y	Rated power ²⁾	Speed	Rated current ^Δ	Rated current ^Y	Rated voltage ^Δ					
			kg	V	V	kW	min ⁻¹	A	A	V	V	kW	min ⁻¹	A	A
63	4	FT100 (C120)	7,1	230	400	0,18	1415	0,96	0,55	–	460	0,21	1725	–	0,56
			5	230	400	0,18	1385	1,07	0,62	–	460	0,21	1685	–	0,60
71	2	FT115 (C140)	7,6	230	400	0,37	2840	1,44	0,83	–	460	0,44	3430	–	0,83
71	2	FT115 (C140)	6	230	400	0,37	2770	1,65	0,95	–	460	0,43	3370	–	0,93
71	4	FT115 (C140)	9,9	230	400	0,25	1430	1,15	0,66	–	460	0,30	1725	–	0,66
71	4	FT115 (C140)	6	230	400	0,25	1395	1,33	0,76	–	460	0,28	1695	–	0,75
71	4	FT115 (C140)	9,9	230	400	0,37	1425	1,74	1,00	–	460	0,44	1720	–	0,98
71	4	FT115 (C140)	7	230	400	0,37	1380	1,77	1,02	–	460	0,43	1680	–	1,04
80	4	FT130 (C160)	10	230	400	0,55	1440	2,40	1,39	–	460	0,63	1735	–	1,42
80	4	FT130 (C160)	11	230	400	0,55	1440	2,20	1,26	–	460	0,55	1740	–	1,25
80	4	FT130 (C160)	14	230	400	0,75	1450	3,05	1,75	–	460	0,86	1750	–	1,72
90	4	FT130 (C160)	16	230	400	1,10	1440	4,20	2,40	–	460	1,27	1740	–	2,40
90	4	FT130 (C160)	19	230	400	1,50	1445	5,50	3,15	–	460	1,75	1740	–	3,15
100	2	FT165 (C200)	25	230	400	3,00	2910	9,90	5,70	–	460	3,45	3505	–	5,60
100	2	FT165 (C200)	26	230	400	3,00	2920	9,80	5,60	–	460	3,45	3520	–	5,50
112	2	FT165 (C200)	32	230	400	4,00	2945	12,80	7,40	–	460	4,55	3545	–	7,30
132	2	FT165 (C200)	48	400	690	5,50	2945	10,10	5,90	460	–	6,30	3540	10,00	–
132	2	FT165 (C200)	43	400	–	5,50	2950	9,90	–	460	–	6,30	3545	9,70	–

1) Flange with threaded hole acc. to DIN EN 50347 (FT).

3) Beyond a performance rating of 0.75 kW, the motors are designed for efficiency class IE3.

IEC squirrel cage motors

Installation drawing and dimensions

Figure 8




Table 8

Dimensions [mm]

Ser.No.	Motor	Frame size	Poles	$\varnothing M$	$\varnothing N$	$\varnothing PM$ ¹⁾	SM	T	A	AA	AB	$\varnothing AC$	AD_{max}	AF_{max}	B	B1	BA	BB
1	178-V12CC-M1...	63	4	100	80	120	M6	3	100	22	120	124	107	85	80	—	—	95
2	178-S22CC-M1...	63	4	100	80	120	M6	3	—	—	—	124	101	77,5	—	—	—	—
3	178-V11ED-M1...	71	2	115	95	140	M8	3	112	32	138	124	107	85	90	—	—	116
4	178-S21ED-M1...	71	2	115	95	140	M8	3	—	—	—	145	111	87,5	—	—	—	—
5	178-V12DD-M1...	71	4	115	95	140	M8	3	112	24	135	139	115	93	90	—	—	114
6	178-S22DD-M1...	71	2	115	95	140	M8	3	—	—	—	145	111	87,5	—	—	—	—
7	178-V12ED-M1...	71	4	115	95	140	M8	3	112	24	135	139	115	93	90	—	—	114
8	178-S22ED-M1...	71	2	115	95	140	M8	3	—	—	—	145	111	87,5	—	—	—	—
9	178-S...	80	4	130	110	160	M8	3	125	30,5	150	159	149,5	112,5	100	—	32	118
10	178-S...	90	4	130	110	160	M8	3,5	140	30,5	165	178	154,5	117,5	100	125	33	143
11	178-S...	100	2	165	130	200	M10	3,5	160	42	196	198	166	125,5	140	—	37,5	176
12	178-S...	112 ²⁾	2	165	130	200	M10	3,5	190	46	226	222	177	136,5	140	—	37,5	176
13	178-S...	132	2	165	130	200	M10	3,5	216	53	256	262	202	159,5	140	—	38	180
Ser.No.	C	H	HA	HD_{max}	K	K1	U		XA_{max}	XB_{max}	HH	LB	L	$\varnothing D$	E	EB	F	GA
1	40	63	7,5	170	$\varnothing 7$	—	1xM20x1,5	92	92	63	176	199	11	23	16	4	12,5	
2	—	—	—	—	—	—	1xM25x1,5	75	75	69,5	205,5	228,5	11	23	16	4	12,5	
3	45	71	11	178	$\varnothing 8$	—	1xM20x1,5	90	90	61	176	206	14	30	22	5	16	
4	—	—	—	—	—	—	1xM25x1,5	75	75	63,5	210	240	14	30	22	5	16	
5	45	71	8	186	$\varnothing 7$	—	1xM20x1,5	90	90	67	209	239	14	30	22	5	16	
6	—	—	—	—	—	—	1xM25x1,5	75	75	63,5	210	240	14	30	22	5	16	
7	45	71	8	186	$\varnothing 7$	—	1xM20x1,5	90	90	67	209	239	14	30	22	5	16	
8	—	—	—	—	—	—	1xM25x1,5	75	75	63,5	210	240	14	30	22	5	16	
9	50	80	8	229,5	9,5	13,5	1xM25x1,5	93	63	73	252	292	19	40	32	6	21,5	
10	56	90	10	244,5	10	14	1xM25x1,5	123	123	78,5	297	347	24	50	40	8	27	
11	63	100	12	266	12	16	2xM32x1,5	135	135	96,5	370,5	430,5	28	60	50	8	31	
12	70	112	12	289	12	16	2xM32x1,5	135	135	96	354	414	28	60	50	8	31	
13	89	132	15	334	12	16	2xM32x1,5	155	155	115,5	385	465	38	80	70	10	41	

1) Mounting flange acc. to DIN 50347.


2) Only standard terminal box position on top is supported, right is not possible.

3) Dimension for 2nd mounting hole

Viscosity-temperature relationship of oils with different rated viscosity

Diagramm 5

Viscosity-temperature relationship of oils



The curves are based on a viscosity index of VI ~ 95, approximately corresponding to standard mineral oil. The viscosity index describes the slope of the curve and thus the viscosity-temperature relationship at temperatures other than +40 °C.

The lines appear straight because a logarithmic scale was selected for the ordinates so that the slope of the curves can be determined easily based on 2 measuring points.

Viscosity class *

ISO VG is approx.

3,10	Spindle oils
32,100	Normal machine oils
320	Medium-heavy machine oils
1000	Gear oil or similar

* The values correspond to the midpoint viscosity at 40 °C in mm²/s



Note
The change in the viscosity of oils is disproportionately greater in lower temperature ranges than in higher temperature ranges. For example, an oil with a rated viscosity of 100 undergoes the following viscosity change in different temperature ranges at the same temperature difference:

at +80 °C = 18 mm²/s

at +75 °C = 21 mm²/s
change of 3 mm²/s


at +10 °C = 875 mm²/s
versus

at + 5 °C = 1450 mm²/s
change of 575 mm²/s

Spare parts

Exploded view

Figure 9



Position description → page 21, table 9.

! Dismantling of the product or individual parts thereof within the statutory warranty period is not permitted and voids any warranty claims..

Spare parts

Table 9

Position description (→ Figure 9)

Gerotor pump unit 1)	Pos. 1 Pump 1)	Pos. 2 Coupling, complete 2)	Pos. 3 Motor	Description	Order No.
143-11...B03C-RA+1GD	143-14...B03	995-000-350	178-V12CC-M1RA+1GD	Docu. package	951-170-251-01
143-12...B03C-XA+1GD	143-14...B03	995-000-350	178-S22CC-M1XA+1GD		
143-11...D03E-RA+1GD	143-14...D03	995-000-351	178-V12DD-M1RA+1GD	Rotation arrow	760-072
143-12...D03E-XA+1GD	143-14...D03	995-000-351	178-S21ED-M1XA+1GD		
143-11...F02D-RA+1GD	143-14...F02	995-000-353	178-V12DD-M1RA+1GD		
143-12...F02D-XA+1GD	143-14...F02	995-000-353	178-S22DD-M1XA+1GD		
143-11...F05F-RA+1GD	143-14...F05	995-000-354	178-S12FE-M1RA+1GD		
143-12...F05F-XA+1GD	143-14...F05	995-000-354	178-S22FE-M1XA+1GD		
143-11...H02F-RA+1GD	143-14...H02	995-000-356	178-S12FE-M1RA+1GD		
143-12...H02F-XA+1GD	143-14...H02	995-000-356	178-S22FE-M1XA+1GD		
143-11...H05J-RA+1GD	143-14...H05	995-000-357	178-S12JE-M1RA+1GD		
143-12...H05J-XA+1GD	143-14...H05	995-000-357	178-S22JE-M1XA+1GD		
143-11...K02H-RA+1GD	143-14...K02	995-000-356	178-S12HE-M1RA+1GD		
143-12...K02H-XA+1GD	143-14...K02	995-000-356	178-S22HE-M1XA+1GD		
143-11...K05J-RA+1GD	143-14...K05	995-000-357	178-S12JE-M1RA+1GD		
143-12...K05J-XA+1GD	143-14...K05	995-000-357	178-S22JE-M1XA+1GD		
143-11...M02H-RA+1GD	143-14...M02	995-000-356	178-S12HE-M1RA+1GD		
143-12...M02H-XA+1GD	143-14...M02	995-000-356	178-S22HE-M1XA+1GD		
143-11...M05K-RA+1GD	143-14...M05	995-000-357	178-S12KE-M1RA+1GD		
143-12...M05K-XA+1GD	143-14...M05	995-000-357	178-S22KE-M1XA+1GD		
143-11...P02K-RA+1GD	143-14...P02	995-000-358	178-S12KE-M1RA+1GD		
143-12...P02K-XA+1GD	143-14...P02	995-000-358	178-S22KE-M1XA+1GD		
143-11...R02M-RA+1GD	143-14...R02	995-000-359	178-S11MF-M1RA+1GD		
143-12...R02M-XA+1GD	143-14...R02	995-000-359	178-S21MF-M1XA+1GD		
143-11...R03M-RA+1GD	143-14...R03	995-000-359	178-S11MF-M1RA+1GD		
143-12...R03M-XA+1GD	143-14...R03	995-000-359	178-S21MF-M1XA+1GD		
143-11...R03N-0A+1GD	143-14...R03	995-000-359	178-S11NF-M10A+1GD		
143-12...R03N-XA+1GD	143-14...R03	995-000-359	178-S21NF-M1XA+1GD		
143-11...T02M-RA+1GD	143-14...T02	995-000-359	178-S11MF-M1RA+1GD		
143-12...T02M-XA+1GD	143-14...T02	995-000-359	178-S21MF-M1XA+1GD		
143-11...T03N-0A+1GD	143-14...T03	995-000-359	178-S11NF-M10A+1GD		
143-12...T03N-XA+1GD	143-14...T03	995-000-359	178-S21NF-M1XA+1GD		
143-11...V02N-0A+1GD	143-14...V02	995-000-359	178-S11NF-M10A+1GD		
143-12...V02N-XA+1GD	143-14...V02	995-000-359	178-S21NF-M1XA+1GD		
143-11...V03N-0A+1GD	143-14...V03	995-000-359	178-S11NF-M10A+1GD		
143-12...V03N-XA+1GD	143-14...V03	995-000-359	178-S21NF-M1XA+1GD		
143-11...V03P-RA+1GD	143-14...V03	995-000-360	178-S11PF-M1RA+1GD		
143-12...V03P-XA+1GD	143-14...V03	995-000-360	178-S21PF-M1XA+1GD		

1) supplement the order No. with the code letter for the desired seal. Design NBR (N) or FKM (F).

2) it is recommended that coupling parts always be replaced completely.

Gerotor pump, product series 143

Comparison of order numbers

Table 10

Comparison of old and new order Nos. for gerotor pump, product series 143

Nominal delivery rate l/min	Back pressure max. bar	Permiss. viscosity range mm ² /s	Sealing design NBR		Sealing design FKM	
			Old order No.	New order No.	Old order No.	New order No.
0.85	30	20–1000	143-011-131	143-14NB03	143-011-132	143-14FB03
1.70	30	20–1000	143-011-131	143-14ND03	143-011-132	143-14FD03
2.50	20	20–1000	143-011-151 1)/-152 2)	143-14NF02 2)	143-011-159 1)	143-14FF02 2)
2.50	50	20–1000	143-011-151 1)/-152 2)	143-14NF05 2)	143-011-159 1)	143-14FF05 2)
5.25	20	20–1000	143-011-161	143-14NH02	143-011-169	143-14FH02
5.25	50	20–1000	143-011-161	143-14NH05	143-011-169	143-14FH05
9.00	20	20–1000	143-011-171	143-14NK02	143-011-173	143-14FK02
9.00	50	20–1000	143-011-171	143-14NK05	143-011-173	143-14FK05
12.50	20	20–1000	143-011-181-2	143-14NM02	143-011-187	143-14FM02
12.50	50	20–1000	143-011-181-2	143-14NM05	143-011-187	143-14FM05
19.00	20	20–1000	143-011-500	143-14NP02	143-011-508	143-14FP02
30.00	20	20–1000	–	143-14NR02	–	143-14FR02
30.00	30	20–750	–	143-14NR03	–	143-14FR03
30.00	30	20–1000	–	143-14NR03	–	143-14FR03
40.00	20	20–750	–	143-14NT02	–	143-14FT02
40.00	30	20–1000	–	143-14NT03	–	143-14FT03
50.00	20	20–1000	–	143-14NV02	–	143-14FV02
50.00	30	20–750	–	143-14NV03	–	143-14FV03
50.00	30	20–1000	–	143-14NV03	–	143-14FV03

1) counterclockwise

2) clockwise

Gerotor pump, product series 143

Comparison of order numbers

Table 11

Comparison of old and new order Nos. for gerotor pump unit in foot design, product series 143

Nominal delivery rate l/min	Back pressure max. bar	Permiss. viscosity range mm ² /s	Sealing design N (NBR)		Sealing design F (FKM)	
			Old order No.	New order No.	Old order No.	New order No.
0.85	30	20–1000	143-012-131+...	143-11NB03C-RA+1GD	–	143-11FB03C-RA+1GD
1.70	30	20–1000	143-012-141+...	143-11ND03E-RA+1GD	143-012-142+...	143-11FD03E-RA+1GD
2.50	20	20–1000	–	143-11NF02D-RA+1GD	–	143-11FF02D-RA+1GD
2.50	50	20–1000	–	143-11NF05F-RA+1GD	–	143-11FF05F-RA+1GD
5.25	20	20–1000	–	143-11NH02F-RA+1GD	–	143-11FH02F-RA+1GD
5.25	50	20–1000	–	143-11NH05J-0A+1GD	–	143-11FH05J-0A+1GD
9.00	20	20–1000	–	143-11NK02H-RA+1GD	–	143-11FK02H-RA+1GD
9.00	50	20–1000	143-012-171+...	143-11NK05J-0A+1GD	–	143-11FK05J-0A+1GD
12.50	20	20–1000	143-012-180+...	143-11NM02H-RA+1GD	–	143-11FM02H-RA+1GD
12.50	50	20–1000	143-012-181+...	143-11NM05K-0A+1GD	–	143-11FM05K-0A+1GD
19.00	20	20–1000	143-012-501+...	143-11NP02K-0A+1GD	143-012-509+...	143-11FP02K-0A+1GD
30.00	20	20–1000	–	143-11NR02M-RA+1GD	–	143-11FR02M-RA+1GD
30.00	30	20–750	–	143-11NR03M-RA+1GD	–	143-11FR03M-RA+1GD
30.00	30	20–1000	–	143-11NR03N-0A+1GD	–	143-11FR03N-0A+1GD
40.00	20	20–750	–	143-11NT02N-0A+1GD	–	143-11FT02N-0A+1GD
40.00	30	20–1000	–	143-11NT03N-0A+1GD	–	143-11FT03N-0A+1GD
50.00	20	20–1000	–	143-11NV02N-0A+1GD	–	143-11FV02N-0A+1GD
50.00	30	20–750	–	143-11NV03N-0A+1GD	–	143-11FV03N-0A+1GD
50.00	30	20–1000	–	143-11NV03P-RA+1GK	–	143-11FV03P-RA+1GK

Table 12

Comparison of old and new order Nos. for gerotor pump unit in flange design, product series 143

Nominal delivery rate l/min	Back pressure max. bar	Permiss. viscosity range mm ² /s	Sealing design N (NBR)		Sealing design F (FKM)	
			Old order No.	New order No.	Old order No.	New order No.
0.85	30	20–1000	143-012-231+...	143-12NB03C-XA+1GD	–	143-12FB03C-XA+1GD
1.70	30	20–1000	143-012-241+...	143-12ND03E-XA+1GD	143-012-242+...	143-12FD03E-XA+1GD
2.50	20	20–1000	–	143-12NF02D-XA+1GD	–	143-12FF02D-XA+1GD
2.50	50	20–1000	–	143-12NF05F-XA+1GD	–	143-12FF05F-XA+1GD
5.25	20	20–1000	–	143-12NH02F-XA+1GD	–	143-12FH02F-XA+1GD
5.25	50	20–1000	–	143-12NH05J-XA+1GD	–	143-12FH05J-XA+1GD
9.00	20	20–1000	–	143-12NK02H-XA+1GD	–	143-12FK02H-XA+1GD
9.00	50	20–1000	143-012-271+...	143-12NK05J-XA+1GD	–	143-12FK05J-XA+1GD
12.50	20	20–1000	143-012-280+...	143-12NM02H-XA+1GD	–	143-12FM02H-XA+1GD
12.50	50	20–1000	143-012-281+...	143-12NM05K-XA+1GD	–	143-12FM05K-XA+1GD
19.00	20	20–1000	143-012-601+...	143-12NP02K-XA+1GD	–	143-12FP02K-XA+1GD
30.00	20	20–1000	–	143-12NR02M-XA+1GD	–	143-12FR02M-XA+1GD
30.00	30	20–750	–	143-12NR03M-XA+1GD	–	143-12FR03M-XA+1GD
30.00	30	20–1000	–	143-12NR03N-XA+1GD	–	143-12FR03N-XA+1GD
40.00	20	20–750	–	143-12NT02M-XA+1GD	–	143-12FT02M-XA+1GD
40.00	30	20–1000	–	143-12NT03N-XA+1GD	–	143-12FT03N-XA+1GD
50.00	20	20–1000	–	143-12NV02N-XA+1GD	–	143-12FV02N-XA+1GD
50.00	30	20–750	–	143-12NV03N-XA+1GD	–	143-12FV03N-XA+1GD
50.00	30	20–1000	–	143-12NV03P-XA+1GK	–	143-12FV03P-XA+1GK

! **Important information on product usage**

SKF and Lincoln lubrication systems or their components are not approved for use with gases, liquefied gases, pressurized gases in solution and fluids with a vapor pressure exceeding normal atmospheric pressure (1 013 mbar) by more than 0,5 bar at their maximum permissible temperature.

skf.com | skf.com/lubrication | skf.com/143

© SKF is a registered trademark of the SKF Group.

SIEMENS is a registered trademark of the Siemens AG.

© SKF Group 2023

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication. However, no liability can be accepted for any loss or damage, whether direct, indirect or consequential, arising out of use of the information contained herein.

PUB LS/P2 14269 EN · 1-1204-3-EN · March 2023